

REPAIRABILITY INDEX CALCULATION AND PRESENTATION OF THE PARAMETERS WHICH ALLOWED TO ESTABLISH IT	<i>Corded vacuum</i>
-----------------------------------------------------------------------------------------------------	----------------------

Date of calculation	18/10/2022
Producer's or importer's name or trademark	RYOBI
Producer or importer adress	35 rue de guivry 77990 Le Mesnil Amelot
Producer's or importer's model identifier	RVC1430PPT-G

This "FINAL_SCORE" tab in English is purely indicative. In order to meet regulatory obligations, only the "NOTE_FINALE" tab in French (see the next tab) is to be sent. Note: The results are automatically reported in the French tab.

(see the next tab) is to be sent. Note: The results are automatically reported in the Fiches tab.

Criteria	Sub-criteria	Score of subcriterion /10	Weighting factor of subcriterion	Score of criterion /20	Total criteria scores /100
CRITERION 1 : DOCUMENTATION	1.1 Availability of the technical documentation and other documentation related to user and maintenance instructions	8,1	2	16,3	71,7
CRITERION 2 : DISASSEMBLY, ACCESSIBILITY, TOOLS, FASTENERS	2.1 Ease of disassembly parts from List 2*	10,0	1	20,0	
	2.2 Necessary tools (List 2)	10,0	0,5		
	2.3 Fasteners characteristics parts from List 1** and List 2	10,0	0,5		
CRITERION 3 : AVAILABILITY OF SPARE PARTS	3.1 Availability over time parts from List 2	6,9	1	15,4	
	3.2 Availability over time parts from List 1	6,9	0,5		
	3.3 Delivery time parts from List 2	10,0	0,3		
	3.4 Delivery time parts from List 1	10,0	0,2		
CRITERION 4 : PRICE OF SPARE PARTS	4. Ratio between price of parts from list 2 to the price of the product	0	2	0	
CRITERION 5 : SPECIFIC CRITERION	5.1 Free remote assistance	10,0	2	20,0	
Reparability index on 10					7,2

* list 2: list of a maximum of 3 to 5 spare parts (depending on the category of equipment concerned) whose broken or malfunctioning parts are the most frequent;

** list 1: list of a maximum of 10 other spare parts (depending on the category of equipment concerned) whose good condition is necessary for the operation of the equipment.